



#### **Features**

- Visible Light Facial Recognition
- Anti-spoofing algorithm against print attack (laser, color and B/W photos), videos attack and 3D mask attack
- Multiple verification methods: Face / Fingerprint / Card / Password
- Available card modules: 125KHz ID card (EM) /13.56MHz IC card (MF)
- Supplement lighting with adjustable brightness
- Capacity of 6,000 face templates

#### 2 meters of recognition distance and extra wide angle recognition

The recognition distance has been greatly extended to 2 meters, which significantly improves maximum traffic rate. While most of the algorithms only support +/-15° of detectable face angle, FaceDepot-7BL doubles the detection angle in terms of head rotation and tilt to +/- 30°.






# **Specifications**

5" touchscreen
6,000
6,000 (Standard); 10,000 (Optional)
10,000
200,000
Linux
ID Card, ADMS, T9 Input, DST, Camera, 9-digit User ID, Access Levels, Groups, Anti-passback, Record Query, Tamper Switch Alarm, Multiple Verify Modes
900MHz Dual Core CPU; 512MB RAM / 8G Flash; 2MP WDR Low Light Camera; Adjustable LED Supplement Lighting
TCP/IP, WiFi (Optional), Wiegand input/output, RS485
3rd Party Electric Lock, Door Sensor, Exit Button, Alarm output, Auxiliary Input
13.56MHz IC card (MF)
≤1s
ZKFace V5.8 & ZKFinger V10.0
12V 3A
20% - 80%
0 °C - 45 °C
134.93 * 166.93 * 21.5 (mm)
ZKBioSecurity, ZKBioAccess, BioTime 8.5


# Configuration



### **Accessories**



## **Dimensions (mm)**





ZKTECO MIDDLE EAST