

UA760

Fingerprint Time & Attendance and Access Control Terminal









UA760 is a 2.8-inch color screen biometric terminal for Time & Attendance, and Access Control (primary) applications. It adopts Z-ID fingerprint collector for excellent recognition and internal WiFi for convenient communication. Users can manage data via TCP/IP, WiFi, and USB host port for data up/download to avoid the risk of accidental deletion. Besides, optional ADMS can achieve remote data management with our ZKBio Time.Net.


Features

- **Wi-Fi:** WiFi module is integrated. It is working on the 2.4G radio band, and meet the IEEE 802.11b/g standards.
- **USB:** Support USB host connection to achieve data backup and management while the device is standalone.
- ADMS: Optional for devices worldwide using. Solve the device's capacity limitation through networking via HTTP sever. Mondial devices can be connected and upload & backup data automatically. This is helpful for devices managing and monitoring.
- Z-ID: Using Z-ID Fingerprint Collector for excellent recognition rate. Dry, moist, or rough fngerprints can work well.


Specifications

User Capacity 3,000		
Card Capacity 3,000 Record Capacity 50,000 Display 2.8" color screen Communication TCP/IP, WiFi, USB-host 14-digit User ID, T9 Input, SMS, DST, Self-Service Query, Automatic Status Switch, Schedule Bell, Workcode, Multiple Verify Modes, RS232 External Printer Optional Functions IC/ID, Webserver, ADMS, Backup Battery, Z-ID Fingerprint Collector Access Control Interface 3rd Party Electirc Lock, Exit Button Software ZKBio Time.Net, ZKBio Time Power Supply DC 12V/1.5A Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 0 °C - 45 °C	User Capacity	3,000
Record Capacity Display 2.8" color screen TCP/IP, WiFi, USB-host 14-digit User ID, T9 Input, SMS, DST, Self-Service Query, Automatic Status Switch, Schedule Bell, Workcode, Multiple Verify Modes, RS232 External Printer Optional Functions IC/ID, Webserver, ADMS, Backup Battery, Z-ID Fingerprint Collector Access Control Interface Software ZKBio Time.Net, ZKBio Time Power Supply DC 12W/1.5A Dimension 186*138*43.6mm (LxWxT) Operating Temp. 0 °C -45 °C	Fingerprint Capacity	3,000
Display 2.8" color screen Communication TCP/IP, WiFi, USB-host 14-digit User ID, T9 Input, SMS, DST, Self-Service Query, Automatic Status Switch, Schedule Bell, Workcode, Multiple Verify Modes, RS232 External Printer Optional Functions IC/ID, Webserver, ADMS, Backup Battery, Z-ID Fingerprint Collector Access Control Interface 3rd Party Electirc Lock, Exit Button Software ZKBio Time.Net, ZKBio Time Power Supply DC 12V/1.5A Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 0 °C - 45 °C	Card Capacity	3,000
Communication TCP/IP, WiFi, USB-host 14-digit User ID, T9 Input, SMS, DST, Self-Service Query, Automatic Status Switch, Schedule Bell, Workcode, Multiple Verify Modes, RS232 External Printer Optional Functions IC/ID, Webserver, ADMS, Backup Battery, Z-ID Fingerprint Collector Access Control Interface 3rd Party Electirc Lock, Exit Button ZKBio Time.Net, ZKBio Time Power Supply DC 12V/1.5A Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 0 °C - 45 °C	Record Capacity	50,000
Standard Functions 14-digit User ID, T9 Input, SMS, DST, Self-Service Query, Automatic Status Switch, Schedule Bell, Workcode, Multiple Verify Modes, RS232 External Printer Optional Functions IC/ID, Webserver, ADMS, Backup Battery, Z-ID Fingerprint Collector Access Control Interface 3rd Party Electirc Lock, Exit Button ZKBio Time.Net, ZKBio Time Power Supply Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 0 °C - 45 °C	Display	2.8" color screen
Switch, Schedule Bell, Workcode, Multiple Verify Modes, RS232 External Printer Optional Functions IC/ID, Webserver, ADMS, Backup Battery, Z-ID Fingerprint Collector Access Control Interface 3rd Party Electirc Lock, Exit Button ZKBio Time.Net, ZKBio Time Power Supply Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. O°C - 45 °C	Communication	TCP/IP, WiFi, USB-host
Access Control Interface Software ZKBio Time.Net, ZKBio Time Power Supply DC 12V/1.5A Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 3rd Party Electirc Lock, Exit Button ZKBio Time DC 12V/1.5A 0°C - 45°C	Standard Functions	
Software ZKBio Time.Net, ZKBio Time Power Supply DC 12V/1.5A Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 0 °C - 45 °C	Optional Functions	IC/ID, Webserver, ADMS, Backup Battery, Z-ID Fingerprint Collector
Power Supply DC 12V/1.5A Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 0 °C - 45 °C	Access Control Interface	3rd Party Electirc Lock, Exit Button
Dimension 186 * 138 * 43.6mm (LxWxT) Operating Temp. 0 °C - 45 °C	Software	ZKBio Time.Net, ZKBio Time
Operating Temp. 0 °C - 45 °C	Power Supply	DC 12V/1.5A
	Dimension	186 * 138 * 43.6mm (LxWxT)
Operating Humidity 20% - 80%	Operating Temp.	0 °C - 45 °C
	Operating Humidity	20% - 80%

Configuration




Interface



What's in the Box


ZKTECO CO., LTD.



UA760







Power Adapter



V4.0 09/08/2023